

## Thermocouple Assemblies Spring-Loaded, High Speed

(20 gage varnished glass insulated wire,  
0.187 inch (4.7 mm) diameter stainless steel tube)

## Model Selection Guide

### Instructions

- Select the Key Number desired. The arrow to the right marks the selections available.
- Make one selection each from Tables I and II using the column below the proper arrow. Select Table V Options if desired.
- A dot denotes unrestricted availability. A letter denotes restricted availability.
- A complete Model Number must have the designated number of digits in each table.

Key Numbers	I	II	III	IV	V (Optional)	
001D20	A1	0	D18.00	L108	C	Example

KEY NUMBER		Selection	Availability			
Mounting	Calibration Type					
Bayonet	T	001D20	↓			
	J	003D20		↓		
Bolt	T	001D21			↓	
	J	003D21				↓

TABLE I - CONSTRUCTION

Maximum Temperature		Construction						
°F	°C							
500	260	Non-Pressure Tight	Straight	A1	•	•		
			Angle	B1	•	•		
		Pressure Tight	Straight	C4	•	•	•	
250	121		Angle	D4	•	•		

TABLE II - HEAD

No Selection		0	•	•		
Screw Cover	Conduit Outlet Size - Inches					
	1/2 NPT	3			•	•
	3/4 NPT	4			•	•

TABLE III - HOLE DEPTH

Hole Depth (inches)	D		•	•	•	•
---------------------	---	--	---	---	---	---

Fill in blanks with hole depth, 1/4" (6,35 mm) increments  
1" (25,4 mm) min. to 18" (457 mm) max.

## Availability




TABLE IV - CABLE LENGTH

	Selection	1	3	1	3
No Selection	0000			•	•
Armored Cable	L _ _ _	•	•		

↑  
 Fill in blanks with cable length, 12" (305 mm) increments  
 12" (305 mm) min. to 120" (3048 mm) max.

TABLE V - OPTIONS

Quik Konnect Plug	C	•	•		
Quik Konnect Jack	D	•	•		
Conduit Fitting, 1/2 inch NPT (#362865-000)	M	•	•		
Tangs (on the ends of the thermocouple wires)	N	Z	Z		
Adapter (1.62 inches long, 1/8 inch NPT)	P	•	•		
Duplex Element	E	•	•	•	•
Duplex Tangs	T	Y	Y	Y	Y

## RESTRICTIONS

Restriction		Available Only With		Not Available With
Letter	Table	Selection	Table	Selection
z			V	E
y	V	E		