

Platinum Resistance Thermometer Bulbs

Type A: 1/4" 316 SS Sheath, 1/2" NPT Mounting Thread, General Purpose Head, 100 OHM @ 0°C (900°F Max.)

Model Number	HP6A1-5-1/2-3A	HP6A1-8-1/2-3A	HP6A1-11-1/2-3A	HP6A1-17-1/2-3A	HP6A1-23-1/2-3A
Immersion Length	5-1/2"	8-1/2"	11-1/2"	17-1/2"	23-1/2"
Add for Screw Cover Head	Change "6" in Model Number to "7"				
Add for S.S. Equip. Tag	Add Suffix "T" to Model Number				

Type D: 1/4" 316 SS Sheath with 18" Teflon Covered Leads, 100 OHM Element @ 0°C (900°F Max.)

Model Number	HP0D1-5-1/2-3A	HP0D1-8-1/2-3A	HP0D1-11-1/2-3A	HP0D1-17-1/2-3A	HP0D1-23-1/2-3A
Sheath Length	5-1/2"	8-1/2"	11-1/2"	17-1/2"	23-1/2"
Extra Lead Length	Standard length 18 inches. For extra lengths up to 6 ft.				
Compression Fitting	Add suffix "C" for 1/4" NPT RC adjustable compression fitting with teflon insert (400°F max.) tight to 1500 PSI and fits over 1/4" nominal O.D. tubing				

Type E: spring Loaded in Specified Well, No Lag, 3/4" NPT Well Thread, Screw Cover Head, 100 OHM Element @ 0 deg C

Model Number	HP7E1-10-1/2-3A*	HP7E1-13-1/2-3A*	HP7E1-16-1/2-3A*	HP7E1-22-1/2-3A*
Immersion Length	4-1/2"	7-1/2"	10-1/2"	16-1/2"
Price for Steel Well (*Add Suffix "1")				
Price for 304 SS Well (*Add Suffix "2")				
Price for 316 SS Well (*Add Suffix "3")				
Add for S.S. Equip. Tag	Add Suffix "T" to Model Number			

Type F: Spring Loaded in Specified Well, 3" Lag, 3/4" NPT Well Thread, Screw Cover Head, 100 OHM Element @ 0 deg C

Model Number	HP7F1-13-1/2-3A*	HP7F1-16-1/2-3A*	HP7F1-19-1/2-3A*	HP7F1-22-1/2-3A*
Immersion Length	4-1/2"	7-1/2"	10-1/2"	13-1/2"
Price for Steel Well (*Add Suffix "1")				
Price for 304 SS Well (*Add Suffix "2")				
Price for 316 SS Well (*Add Suffix "3")				
Add for S.S. Equip. Tag	Add Suffix "T" to Model Number			

Type G: 3/16" SS Sheath, 2-1/2" Long with 60" Teflon Covered Leads (450°F Max.)

Model Number	HP0G1-2-1/2-3B
Ohms per Element	100
Number of Elements	1
Extra 5 ft. lengths	