

SFC Smart Field Communicator

Model Selection Guide With Price Data

Model Selection Guide
34-ST-16U-08 Issue 22

Honeywell Confidential & Proprietary

Instructions

- Select the desired Key Number. The arrow to the right marks the selection available.
- Make one selection from each table, I and II, using the column below the proper arrow. Select as many Table III options as desired (if no options are desired, specify 00). A dot denotes unrestricted availability. A letter denotes restricted availability. Restrictions follow Table IV.

Key Number I II III (Optional) IV
 [] - [] - [] - [] + []

KEY NUMBER

Design Style	Selection	Availability
Smart Field Communicator	STS103	↓


TABLE I

Display Language	English	001	•
	German	002	•
	Spanish	003	•
	French	005	•

TABLE II

Cable Length	6 Feet	00006	•
--------------	--------	-------	---

TABLE III OPTIONS

None		00	•	
Battery Charger - 120 VAC 50/60 Hz		12	•	b
Battery Charger - 240 VAC 50/60 Hz		24	•	
Digital Mode Certification		DC	•	b
Certificate of Conformance (F3391)		F3	•	
Certificate of Origin (F0195)		F5	•	
Approval Body	Approval Type	Location or Classification		
Factory Mutual	Intrinsically Safe	Class I, II, III, Div. 1 Groups A,B,C,D,E,F,G	1S	•
CSA	Intrinsically Safe	Class I, II, III, Div. 1 Groups A,B,C,D,F,G	2S	•
SA (Australia)	Intrinsically Safe Non-Sparking	Ex ia IIC T6 Ex n IIC T6	4G	•
ATEX*	Intrinsically Safe, Zone0/1	 II 1 G EEx ia IIC T5	3S	•

*See ATEX installation requirements in the ST 3000 User's Manual

Industrial Measurement and Control, 16404 North Black Canyon Highway, Phoenix, AZ 85053

Printed in U.S.A. Copyright 2002 - Honeywell International Inc.

TABLE IV

Factory Identification	XXXX	•
------------------------	------	---

The STS103 is now shipped with software version 5.3 to support all Smartline Field Instruments.

RESTRICTIONS

Restriction		Available Only With		Not Available With
Letter	Table	Selection	Table	Selection
b	Select only one option from this group.			

Example: STS103-001-00006-12 + XXXX