

Series 900 Smart Transmitter Replacement Meter Bodies - R300 Differential Pressure (DP)

Model Selection Guide With Price Data

Model Selection Guide
34-ST-16U-25 Issue 15

Honeywell Confidential & Proprietary

Instructions

- These replacement meter bodies are for ST 3000 Release 300 (R300) only.
- Select the desired Key Number per 13:ST-OD-3. The arrow to the right marks the selection available.
- Make one selection from each table, I and II, using the column below the proper arrow. A (♦) denotes unrestricted availability. A letter denotes restricted availability. Restrictions follow Table IV.

Key Number I II III IV
 [] - [] - [] - [00] + [X X X X]

KEY NUMBER	Selection	Availability		
Span				
0-10" to 0-400" H ₂ O/0-25 to 0-1000 mbar	STD924R	↓		
0-5 psi to 0-100 psi/0-0.34 to 0-7 bar	STD930R		↓	
0-100 psi to 0-3000 psi/0-7 to 0-210 bar	STD974R			↓

TABLE I - METER BODY

	Process Heads	Vent/Drain Valves and Plugs	Barrier Diaphragms				
Material of Construction	---	---	316 LSS	A _ _	♦	♦	♦
	---	---	Hastelloy C	B _ _	♦	♦	♦
	---	---	Monel	C _ _	♦		
	---	---	Tantalum	D _ _	♦	♦	
Fill Fluid	Silicone			_ 1 _	♦	♦	♦
	CTFE			_ 2 _	♦	♦	♦
No Selection	None			_ _ 0	♦	♦	♦

TABLE II

No Selection	00000	♦	♦	♦
--------------	-------	---	---	---

TABLE III - OPTIONS

	Selection			
No Selection	00	♦	♦	♦

TABLE IV

Factory Identification	XXXX	♦	♦	♦
------------------------	------	---	---	---

Next Page Blank

This page intentionally blank